

# Really Naturally Linear Indexed Type Checking

Arthur Azevedo de Amorim<sup>1</sup>, Marco Gaboardi<sup>2</sup>,  
Emilio Jesús Gallego Arias<sup>1</sup>, Justin Hsu<sup>1</sup>

<sup>1</sup>University of Pennsylvania

<sup>2</sup>University of Dundee

October 2, 2014

In the beginning...

In the beginning...





## Check properties via types

- Type safety
- Parametricity
- Non-interference


## Properties model quantitative information

- Numerical robustness
- Probabilistic assertions
- Differential privacy


## Properties model quantitative information

- Numerical robustness  how robust?
- Probabilistic assertions
- Differential privacy


## Properties model quantitative information

- Numerical robustness  how robust?
- Probabilistic assertions  how likely?
- Differential privacy

## Properties model quantitative information

- Numerical robustness  how robust?
- Probabilistic assertions  how likely?
- Differential privacy  how private?

## Properties model quantitative information

- Numerical robustness  how robust?
- Probabilistic assertions  how likely?
- Differential privacy  how private?

Properties not just true or false

# But what about typechecking?

Typechecking quantitative languages is tricky

- May need to solve numeric constraints
- Typechecking may not be decidable
- May need heuristics to make typechecking practical

# But what about typechecking?

## Typechecking quantitative languages is tricky

- May need to solve numeric constraints
- Typechecking may not be decidable
- May need heuristics to make typechecking practical

## Our goal



- Design and implement a typechecking algorithm for DFuzz, a language for verifying differential privacy

- A DFuzz crash course
- The problem with standard approaches
- Modifying the DFuzz language to ease typechecking
- Decidability and heuristics


## Differential privacy [DMNS06]

- Rigorous definition of privacy for randomized programs
- Idea: random noise should “conceal” an individual’s data
- Quantitative: measure **how private** a program is
- Close connection to **sensitivity analysis**


$R$ -sensitive function




$R$ -sensitive function




*R*-sensitive function




$R$ -sensitive function



$R$ -sensitive function



$R$ -sensitive function



## DFuzz [GHHNP13]

- Type system for differentially private programs
- Use linear logic to model sensitivity
- Combine with (lightweight) dependent types

## Types

$$\tau ::= \mathbb{N} \mid [R] \mid \tau \oplus \tau \mid \tau \otimes \tau \mid ! \tau \mid \tau \multimap \tau \mid \forall i. \tau$$

## Types

$$\tau ::= \mathbb{N} [R] \mid \tau \oplus \tau \mid \tau \otimes \tau \mid !_R \tau \multimap \tau \mid \forall i. \tau$$

## Contexts

$$\Gamma ::= \cdot \mid \Gamma, x : [R] \tau$$

## Types

$$\tau ::= \mathbb{N} \ [R] \mid \tau \oplus \tau \mid \tau \otimes \tau \mid ! \ _R \tau \multimap \tau \mid \forall i. \tau$$

## Contexts

$$\Gamma ::= \cdot \mid \Gamma, x : \[_R] \tau$$


## Typing judgment

$$\Gamma \vdash e : \tau$$

## Sensitivity reading

- Functions  $!_R \tau_1 \multimap \tau_2$ : *R-sensitive functions*
- Changing input by  $d$  changes output by at most  $R \cdot d$

$R$ -sensitive function



## Sensitivity reading

- Functions  $!_R \tau_1 \multimap \tau_2$ : *R-sensitive functions*
- Changing input by  $d$  changes output by at most  $R \cdot d$

## Sensitivity reading

- Functions  $!_R \tau_1 \multimap \tau_2$ : *R-sensitive functions*
- Changing input by  $d$  changes output by at most  $R \cdot d$

## Subtyping

- “A 1-sensitive function is also a 2-sensitive function”
- Subtyping: weaken sensitivity bound

$$!_R \tau_1 \multimap \tau_2 \sqsubseteq !_{R'} \tau_1 \multimap \tau_2 \quad \text{if} \quad R \leq R'$$

## Types

$$\tau ::= \mathbb{N} \ [R] \mid \tau \oplus \tau \mid \tau \otimes \tau \mid ! \ _R \tau \multimap \tau \mid \forall i. \tau$$

## Contexts

$$\Gamma ::= \cdot \mid \Gamma, x : \ _R \tau$$

## Typing judgment

$$\Gamma \vdash e : \tau$$

## Types

$$\tau ::= \mathbb{N} [R] \mid \tau \oplus \tau \mid \tau \otimes \tau \mid ! [R] \tau \multimap \tau \mid \forall i. \tau$$

## Contexts

$$\Gamma ::= \cdot \mid \Gamma, x : [R] \tau$$

## Typing judgment

$$\Gamma \vdash e : \tau$$

## Grammar

$$R ::= i_{\mathbb{R}} \mid i_{\mathbb{N}} \mid \mathbb{R} \mid R + R \mid R \cdot R$$

## Grammar

$R ::= i_{\mathbb{R}} \mid i_{\mathbb{N}} \mid \mathbb{R} \mid R + R \mid R \cdot R$

variables over  
real/naturals

## Grammar

$$R ::= i_{\mathbb{R}} \mid i_{\mathbb{N}} \mid \mathbb{R} \mid R + R \mid R \cdot R$$

variables over  
real/naturals

## Sensitivity not known statically

- DFuzz is dependent!
- Sensitivity may depend on inputs (length of list, number of iterations, etc.)

## Types

$$\tau ::= \mathbb{N} [R] \mid \tau \oplus \tau \mid \tau \otimes \tau \mid ! [R] \tau \multimap \tau \mid \forall i. \tau$$

## Contexts

$$\Gamma ::= \cdot \mid \Gamma, x : [R] \tau$$

## Typing judgment

$$\Gamma \vdash e : \tau$$

## Grammar

$$R ::= i_{\mathbb{R}} \mid i_{\mathbb{N}} \mid \mathbb{R} \mid R + R \mid R \cdot R$$

variables over  
real/naturals

## Sensitivity not known statically

- DFuzz is dependent!
- Sensitivity may depend on inputs (length of list, number of iterations, etc.)

## Grammar

$$R ::= i_{\mathbb{R}} \mid i_{\mathbb{N}} \mid \mathbb{R} \mid R + R \mid R \cdot R$$

variables over  
real/naturals

## Sensitivity not known statically

- DFuzz is dependent!
- Sensitivity may depend on inputs (length of list, number of iterations, etc.)

## What does this mean for typechecking?

- Sensitivities are **polynomials** over reals and naturals
- How to check subtyping?

## Sensitivity reading

- Functions  $!_R \tau_1 \multimap \tau_2$ : *R-sensitive functions*
- Changing input by  $d$  changes output by at most  $R \cdot d$

## Subtyping

- “A 1-sensitive function is also a 2-sensitive function”
- Subtyping: weaken sensitivity bound

$$!_R \tau_1 \multimap \tau_2 \sqsubseteq !_{R'} \tau_1 \multimap \tau_2 \quad \text{if} \quad R \leq R'$$

## Sensitivity reading

- Functions  $!_R \tau_1 \multimap \tau_2$ : *R-sensitive functions*
- Changing input by  $d$  changes output by at most  $R \cdot d$

## Subtyping

- “A 1-sensitive function is also a 2-sensitive function”
- Subtyping: weaken sensitivity bound

$$!_R \tau_1 \multimap \tau_2 \sqsubseteq !_{R'} \tau_1 \multimap \tau_2 \quad \text{if}$$

$$R \leq R'$$

compare  
polynomials

## Assume

- Can extract type skeleton from term
- Given annotated term, compute best type

## Assume

- Can extract type `skeleton` from term
- Given annotated term, compute `best` type

# The typechecking problem

## Assume

- Can extract type **skeleton** from term
- Given annotated term, compute **best** type

type without sensitivities

# The typechecking problem

## Assume

- Can extract type **skeleton** from term
- Given annotated term, compute **best** type

type without sensitivities

# The typechecking problem

## Assume

- Can extract type **skeleton** from term
- Given annotated term, compute **best** type

type without sensitivities

w.r.t. subtyping

# The typechecking problem

## Assume

- Can extract type skeleton from term
- Given annotated term, compute best type

## Annotations

- We need: fully annotated argument types of all functions

$$! \quad ?? \quad \tau_1 \multimap \tau_2$$

# The typechecking problem

## Assume

- Can extract type skeleton from term
- Given annotated term, compute best type

## Annotations

- We need: fully annotated argument types of all functions

! ??  $\tau_1 \multimap \tau_2$

annot.

# The typechecking problem

## Assume

- Can extract type skeleton from term
- Given annotated term, compute best type

## Annotations

- We need: fully annotated argument types of all functions




# The typechecking problem

## Assume

- Can extract type skeleton from term
- Given annotated term, compute best type

## Annotations

- We need: fully annotated argument types of all functions




# The typechecking problem

## Assume

- Can extract type skeleton from term
- Given annotated term, compute best type

## Annotations

- We need: fully annotated argument types of all functions



- Other more minor annotations

## Input

- Annotated term  $e$
- Annotated **context skeleton**  $\Gamma^\bullet$ :

$$x : ?? \quad \tau$$

## Input

- Annotated term  $e$
- Annotated **context skeleton**  $\Gamma^\bullet$ :


$x : \text{??} \tau$

no annot.

# The typechecking problem

## Input


- Annotated term  $e$
- Annotated **context skeleton**  $\Gamma^\bullet$ :



# The typechecking problem

## Input

- Annotated term  $e$
- Annotated **context skeleton**  $\Gamma^\bullet$ :



## Output

- Type  $\tau^*$  and context  $\Gamma$  with  $\Gamma \vdash e : \tau^*$
- Most precise context and type (with respect to subtyping)

## “Bottom-up” typechecking

- For each premise, compute best context and type
- Combine outputs from premises to get context and type

## “Bottom-up” typechecking

- For each premise, compute best context and type
- Combine outputs from premises to get context and type

## Example: function application

$$\frac{\Gamma \vdash e_1 : !_R \sigma \multimap \tau \quad \Delta \vdash e_2 : \sigma}{\Gamma + R \cdot \Delta \vdash e_1 e_2 : \tau}$$

- 1 Given  $(e_1 e_2, \Gamma^\bullet)$

## “Bottom-up” typechecking

- For each premise, compute best context and type
- Combine outputs from premises to get context and type

## Example: function application

$$\frac{\Gamma \vdash e_1 : !_R\sigma \multimap \tau \quad \Delta \vdash e_2 : \sigma}{\Gamma + R \cdot \Delta \vdash e_1 e_2 : \tau}$$

- 1 Given  $(e_1 e_2, \Gamma^\bullet)$
- 2 Call typechecker on  $(e_1, \Gamma^\bullet)$ , get  $(!_R\sigma \multimap \tau, \Gamma)$

## “Bottom-up” typechecking

- For each premise, compute best context and type
- Combine outputs from premises to get context and type

## Example: function application

$$\frac{\Gamma \vdash e_1 : !_R\sigma \multimap \tau \quad \Delta \vdash e_2 : \sigma}{\Gamma + R \cdot \Delta \vdash e_1 e_2 : \tau}$$

- 1 Given  $(e_1 e_2, \Gamma^\bullet)$
- 2 Call typechecker on  $(e_1, \Gamma^\bullet)$ , get  $(!_R\sigma \multimap \tau, \Gamma)$
- 3 Call typechecker on  $(e_2, \Delta^\bullet)$ , get  $(\sigma', \Delta)$

## “Bottom-up” typechecking

- For each premise, compute best context and type
- Combine outputs from premises to get context and type

## Example: function application

$$\frac{\Gamma \vdash e_1 : !_R \sigma \multimap \tau \quad \Delta \vdash e_2 : \sigma}{\Gamma + R \cdot \Delta \vdash e_1 e_2 : \tau}$$

- 1 Given  $(e_1 e_2, \Gamma^\bullet)$
- 2 Call typechecker on  $(e_1, \Gamma^\bullet)$ , get  $(!_R \sigma \multimap \tau, \Gamma)$
- 3 Call typechecker on  $(e_2, \Delta^\bullet)$ , get  $(\sigma', \Delta)$
- 4 Check  $\sigma' \sqsubseteq \sigma$ , output  $(\tau, \Gamma + R \cdot \Delta)$

## A problem with the bottom-up approach

- Some DFuzz rules have form

$$\frac{\Gamma \vdash e_1 : \sigma_1 \quad \Gamma \vdash e_2 : \sigma_2}{\Gamma \vdash \dots : \dots}$$

## A problem with the bottom-up approach

- Some DFuzz rules have form

$$\frac{\Gamma \vdash e_1 : \sigma_1 \quad \Gamma \vdash e_2 : \sigma_2}{\Gamma \vdash \dots : \dots}$$

## A problem with the bottom-up approach

- Some DFuzz rules have form

$$\frac{\Gamma \vdash e_1 : \sigma_1 \quad \Gamma \vdash e_2 : \sigma_2}{\Gamma \vdash \dots : \dots}$$

## A problem with the bottom-up approach

- Some DFuzz rules have form

$$\frac{\Gamma \vdash e_1 : \sigma_1 \quad \Gamma \vdash e_2 : \sigma_2}{\Gamma \vdash \dots : \dots}$$

- Running algorithm gives  $(\sigma_1, \Gamma_1)$  and  $(\sigma_2, \Gamma_2)$

## A problem with the bottom-up approach

- Some DFuzz rules have form

$$\frac{\Gamma \vdash e_1 : \sigma_1 \quad \Gamma \vdash e_2 : \sigma_2}{\Gamma \vdash \dots : \dots}$$

- Running algorithm gives  $(\sigma_1, \Gamma_1)$  and  $(\sigma_2, \Gamma_2)$
- But what context do we output?

## First try

- Have  $x : [R_1] \sigma$  and  $x : [R_2] \sigma$
- Most precise context should be  $x : [\mathbf{max}(R_1, R_2)] \sigma$
- But DFuzz doesn't have  $\mathbf{max}(R_1, R_2) \dots$

## Grammar

$$R ::= i_{\mathbb{R}} \mid i_{\mathbb{N}} \mid \mathbb{R} \mid R + R \mid R \cdot R$$

## First try

- Have  $x : [R_1] \sigma$  and  $x : [R_2] \sigma$
- Most precise context should be  $x : [\mathbf{max}(R_1, R_2)] \sigma$
- But DFuzz doesn't have  $\mathbf{max}(R_1, R_2) \dots$

## First try

- Have  $x : [R_1] \sigma$  and  $x : [R_2] \sigma$
- Most precise context should be  $x : [\mathbf{max}(R_1, R_2)] \sigma$
- But DFuzz doesn't have  $\mathbf{max}(R_1, R_2) \dots$

Max of two polynomials may not be polynomial!

## EDFuzz: E(xtended) DFuzz

- Sensitivity language in DFuzz is “incomplete” for typechecking
- Add constructions like **max**( $R_1, R_2$ ) to sensitivity language
- Typecheck EDFuzz programs instead

## EDFuzz: E(xtended) DFuzz

- Sensitivity language in DFuzz is “incomplete” for typechecking
- Add constructions like  $\mathbf{max}(R_1, R_2)$  to sensitivity language
- Typecheck EDFuzz programs instead

## Relation with DFuzz

- Extension: all DFuzz programs still valid EDFuzz programs
- Preserve metatheory
- Bottom-up typechecking simple, works

## How does this fix the problem?

Previously problematic rule

$$\frac{\Gamma \vdash e_1 : \sigma_1 \quad \Gamma \vdash e_2 : \sigma_2}{\Gamma \vdash \dots : \dots}$$

## How does this fix the problem?

Previously problematic rule

$$\frac{\Gamma \vdash e_1 : \sigma_1 \quad \Gamma \vdash e_2 : \sigma_2}{\Gamma \vdash \dots : \dots}$$

Now: no problem

- Running algorithm gives  $(\sigma_1, \Gamma_1)$  and  $(\sigma_2, \Gamma_2)$

## How does this fix the problem?

Previously problematic rule

$$\frac{\Gamma \vdash e_1 : \sigma_1 \quad \Gamma \vdash e_2 : \sigma_2}{\Gamma \vdash \dots : \dots}$$

Now: no problem

- Running algorithm gives  $(\sigma_1, \Gamma_1)$  and  $(\sigma_2, \Gamma_2)$

# How does this fix the problem?

Previously problematic rule

$$\frac{\Gamma \vdash e_1 : \sigma_1 \quad \Gamma \vdash e_2 : \sigma_2}{\Gamma \vdash \dots : \dots}$$

Now: no problem

- Running algorithm gives  $(\sigma_1, \Gamma_1)$  and  $(\sigma_2, \Gamma_2)$

# How does this fix the problem?

Previously problematic rule

$$\frac{\Gamma \vdash e_1 : \sigma_1 \quad \Gamma \vdash e_2 : \sigma_2}{\Gamma \vdash \dots : \dots}$$

Now: no problem

- Running algorithm gives  $(\sigma_1, \Gamma_1)$  and  $(\sigma_2, \Gamma_2)$
- For

$$x :_{[R_1]} \sigma \in \Gamma_1 \quad \text{and} \quad x :_{[R_2]} \sigma \in \Gamma_2,$$

put  $x :_{[\max(R_1, R_2)]} \sigma$  in output context

# How does this fix the problem?

Previously problematic rule

$$\frac{\Gamma \vdash e_1 : \sigma_1 \quad \Gamma \vdash e_2 : \sigma_2}{\Gamma \vdash \dots : \dots}$$

Now: no problem

- Running algorithm gives  $(\sigma_1, \Gamma_1)$  and  $(\sigma_2, \Gamma_2)$
- For

$$x :_{[R_1]} \sigma \in \Gamma_1 \quad \text{and} \quad x :_{[R_2]} \sigma \in \Gamma_2,$$

put  $x :_{[\max(R_1, R_2)]} \sigma$  in output context

- Return  $\max(R_1, R_2)$  as context

## Bad news

- Must check inequalities over reals and natural polynomials
- Subtype relation is undecidable
- Even checking validity of derivations is undecidable
- Problem for both DFuzz and EDFuzz

## Bad news

- Must check inequalities over reals and natural polynomials
- Subtype relation is undecidable
- Even checking validity of derivations is undecidable
- Problem for both DFuzz and EDFuzz

## Good news

- Constraint solvers are pretty good in practice
- Typical DFuzz programs rely on easy constraints

## Special structure of constraints

- Allow standard (DFuzz) annotations only
- Subtyping only needs to check

$$R \geq R^*,$$

where  $R$  is a DFuzz sensitivity and  $R^*$  is a EDFuzz sensitivity

- $R$  understood by standard numeric solvers
- $R^*$  has extended terms like  $\mathbf{max}(R_1, R_2), \dots$

Idea: eliminate extended terms

- Change  $R \geq \mathbf{max}(R_1^*, R_2^*)$  to

$$R \geq R_1^* \wedge R \geq R_2^*$$

- Recursively eliminate comparisons  $R \geq R^*$
- Similar technique for other new sensitivity constructions

It works!

- Dispatches numeric constraints to Why3
- Typechecks examples from the DFuzz paper with no problems
- Annotation burden light on these examples

## Lessons learned

- Typechecking with quantitative constraints is tricky
- Numeric solvers are quite good, even for undecidable problems
- Minor details in original language can have huge effects on how easy it is to use standard solvers
- Keep typechecking in mind!

## Lessons learned

- Typechecking with quantitative constraints is tricky
- Numeric solvers are quite good, even for undecidable problems
- Minor details in original language can have huge effects on how easy it is to use standard solvers
- Keep typechecking in mind!

## Open questions

- Does this technique of “completing” a language to ease typechecking apply to other quantitative type systems?
- Can we remove the argument type annotation in functions?

# Really Naturally Linear Indexed Type Checking

Arthur Azevedo de Amorim<sup>1</sup>, Marco Gaboardi<sup>2</sup>,  
Emilio Jesús Gallego Arias<sup>1</sup>, Justin Hsu<sup>1</sup>

<sup>1</sup>University of Pennsylvania

<sup>2</sup>University of Dundee

October 2, 2014

## Problematic rule

$$\frac{\Gamma \vdash e : \sigma \quad i \text{ fresh in } \Gamma}{\Gamma \vdash \Lambda i : \kappa. e : \forall i : \kappa. \sigma}$$

## Avoidance problem

- Running typechecker on  $(e, \Gamma^\bullet)$  yields  $(\sigma, \Gamma)$
- For  $x :_{[R]} \sigma \in \Gamma$ , want smallest  $R^*$  bigger than  $R$  but independent of  $i$
- Again:  $R^*$  may lie outside sensitivity language
- Add construction  $\mathbf{sup}(R, i)$  to EDFuzz